



## **Mod. ZEFIRO101**

### **CONTINUOUS DUTY WET & DRY INDUSTRIAL VACUUM CLEANER**



MODEL		ZEFIRO 101
Tension	Volts HZ	230 – 400 3~ 50 /60
Power	KW / Hp	5,5 / 7,5
Max. Vacuum rate	mm.H <sub>2</sub> O	3200
Max. vacuum rate on continuous duty	mm.H <sub>2</sub> O	2200
Max. Air flow rate**	M <sup>3</sup> /h	600
Filter surface (pocket filter)	Cm <sup>2</sup>	30.000
Filter efficiency	CAT BIA Micron	L > 3
Air load on filter	M <sup>3</sup> /M <sup>2</sup> /h	200
Capacity	Lt.	100
Suction inlet	Ø	80
Noise level	dB(A)	76
Protection	IP	55
Dimensions	cm.	80 x 80
Height	cm.	180
Weight	Kg.	120

#### **Suction unit**

The suction is provided by a suction unit of the side channel blower type, with direct coupling between the fan and the motor shaft and no transmission system. It is thus completely maintenance free, fit for round-the-clock 24 hours duty, very silent and provides outstanding suction performances. A vacuum indicator enables constant checking of the suction performance, and to detect possible clogging of the filter. A **diffuser filter** reduces the speed and noise of the air on the exhaust outlet.

#### **Filter unit**

The **polyester star filter**, placed and protected inside the steel filter chamber, **provides a filter surface of 30.000 cm<sup>2</sup>**, and high **filtration efficiency (class L, 3 micron)**. A manual filter shaker enables the user to clean the filter efficiently, by a vertical shaking movement, so as to detach most of the dust and maintain the filter clean, in order to increase its life and maintain the suction performance of the machine.

The frontal aluminium die-cast suction inlet (Ø80 mm. diameter), placed below the filter, makes it possible to vacuum at the same time dust, solid and liquid material (the latter only within the capacity of the container), with no need to change or take out the filter. Thanks to the tilting filter chamber, it is possible to inspect or change the filter without removing the motor head.

#### **Collection unit**

The vacuumed material is placed inside a detachable bin mounted on wheels (100 litres capacity), which makes it possible to dispose easily and safely of the sucked material, that can be collecting directly into a plastic bag.

The vacuum is mounted on a sturdy steel chassis with two pivoting wheels, one of which with brakes; all metal parts of the vacuum are epoxy painted.



## Options\*

Application	Code	Description
Fine dust	C	Pocket filter with 1 micron efficiency
Sticky dust and material	PTFE	PTFE treated pocket filter (reduces the adherence of the dust on the filter)
High temperature dust and material	NOMEX	Nomex flame proof filter, resistano up to 250° C temperatures
Dust and material subject to accumulate static electricity	ANT	Antistatic pocket filter
Fine dust subject to accumulate static electricity	ANT/C	Antistatic pocket filter, 1 micron efficiency
Corrosive dust and material	X	Stainless steel container AISI304
Corrosive dust and material	XX	Stainless steel container and filter chamber AISI304

\* Different combinations of the above options are possible (e.g. ACX , vacuum with Absolute filter, 1 micron pocket filter and stainless steel container)